

Cambiar IP por default de los equipos TP-Link.

1.- Abrir una ventana de navegador y escribir <http://192.168.0.1> (IP default). Al ingresar usuario y contraseña, nos envía en pantalla la información general del equipo.

The screenshot shows the web interface for a TP-Link TL-SG2216 switch. The 'System Summary' tab is active, displaying a port diagram and system information. The port diagram shows 16 ports (1-16T) and two SFP slots (15F, 16F). The system information table is as follows:

System Info	
System Description:	16-Port Gigabit Smart Switch with 2 Combo SFP Slots
Device Name:	TL-SG2216
Device Location:	SHENZHEN
System Contact:	www.tp-link.com
Hardware Version:	TL-SG2216 2.0
Firmware Version:	1.0.0 Build 20140630 Rel.33944(s)
IP Address:	192.168.0.1
Subnet Mask:	255.255.255.0
Default Gateway:	
MAC Address:	30-B5-C2-F9-B4-D1
System Time:	2006-01-01 08:16:27
Run Time:	0 day - 0 hour - 16 min - 35 sec

Buttons for 'Refresh' and 'Help' are visible at the bottom of the system info section.

2.- Ingresamos en la pestaña de "System IP".

The screenshot shows the 'System IP' configuration page for the TL-SG2216 switch. The 'System IP' tab is highlighted in red. The configuration fields are as follows:

IP Config	
MAC Address:	30-B5-C2-F9-B4-D1
IP Address Mode:	<input checked="" type="radio"/> Static IP <input type="radio"/> DHCP <input type="radio"/> BOOTP
Management VLAN:	<input type="text" value="1"/> (VLAN ID: 1-4094)
IP Address:	<input type="text" value="192.168.0.1"/>
Subnet Mask:	<input type="text" value="255.255.255.0"/>
Default Gateway:	<input type="text"/>

'Apply' and 'Help' buttons are located to the right of the IP Address and Subnet Mask fields. A note at the bottom states: "Note: Changing IP address to a different IP segment will interrupt the network communication, so please keep the new IP address in the same IP segment with the local network."

3.- Habilitamos la opción de **IP estática**, **DHCP** o **BOOTP**, según sea el caso. Para confirmar los cambios damos click en **Apply**.

System Summary Device Description System Time Daylight Saving Time System IP System IPv6

IP Config

MAC Address:	30-B5-C2-F9-B4-D1
IP Address Mode:	<input type="radio"/> Static IP <input checked="" type="radio"/> DHCP <input type="radio"/> BOOTP
Management VLAN:	<input type="text" value="1"/> (VLAN ID: 1-4094)
IP Address:	<input type="text" value="192.168.0.1"/>
Subnet Mask:	<input type="text" value="255.255.255.0"/>
Default Gateway:	<input type="text"/>

Note:

Changing IP address to a different IP segment will interrupt the network communication, so please keep the new IP address in the same IP segment with the local network.